

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012



## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** R-Y1 Rolmark Yellow Stencil Ink
- **Article number:** PRODUCT CODES: 20900,20926,1F153,33567
- **Application of the substance / the preparation** Printing inks
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Marsh Shipping Supply Co.,LLC  
926 McDonough Lake Road - Unit E  
Collinsville, IL 62234  
USA
- **Information department:** customerservice@mssllc.com
- **Emergency telephone number:**  
Chemtrec 800-424-9300  
International 703-527-3887

## 2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### · Hazardous components

|             |  |   |        |
|-------------|--|---|--------|
| 123-42-2    | 4-hydroxy-4-methylpentan-2-one   |  Xi R36<br> H319 | 65.74% |
| 5468-75-7   | Yellow AAOT Pigment 14   |   | 11.0%  |
|             | Modified Rosin Ester NJ TSRN 80100080-5097P<br>EINECS polymer exempt - all components listed |   | 3.97%  |
| 112945-52-5 | Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free                                    |   | 0.22%  |

### · Additional information:

This product contains pigments which may become a dust nuisance when removed by abrasive blasting or sanding. Airborne nuisance particulates have an ACGIH TLV for total dust of 10mg/M3

## 3 Hazards identification

- **Classification of the substance or mixture**



GHS02 Flame

H226 Flammable liquid and vapour.



GHS07

H319 Causes serious eye irritation.

H333 May be harmful if inhaled.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Read MSDS before using

**WARNING! FLAMMABLE LIQUID. HARMFUL.** Keep liquid and vapors away from ignition sources, heat, and static discharge. Avoid contact with eyes and skin. Avoid inhalation of mist or vapor.

**NOTICE-**For professional users only! This material is intended for use by trained professional applicators, only after carefully examining this MSDS and evaluating safety precautions associated with the use of this material.

(Contd. on page 2)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

Trade name: R-Y1 Rolmark Yellow Stencil Ink

(Contd. of page 1)



Xi; Irritant

R36: Irritating to eyes.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

- **Classification system:**

The classification was made according to the latest editions of international substances lists and from component data and msds information

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

- **Code letter and hazard designation of product:**

Xi Irritant

- **Risk phrases:**

36 Irritating to eyes.

- **Safety phrases:**

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36 Wear suitable protective clothing.

51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

- **Information pertaining to particular dangers for man and environment:**

- **Potential Chronic Health Effects**

Prolonged or repeated exposure of vapors, spray, or material may cause diseases of the lungs. Reports have associated repeated overexposure to solvents with brain and nervous system damage. Intentional misuse of this product may be harmful or fatal.

- **Target Organs**

Overexposure to this material or its components has been suggested as a cause of the following effects in laboratory animals and/or humans, and may aggravate preexisting disorders of these organs in humans: Anemia, Blood disorders, Brain damage, Cardiac function, eye, liver, lung, menstrual and fertility, skin, respiratory, Central Nervous System

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 2

Reactivity = 0

## 4 First aid measures

- **General information:**

Take affected persons out into the fresh air.

Involve doctor immediately.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

**Trade name: R-Y1 Rolmark Yellow Stencil Ink**

(Contd. of page 2)

- **After skin contact:** Immediately rinse with water for 15 minutes. If irritation exists call physician.
- **After eye contact:**  
Rinse opened eye for fifteen minutes under running water. If irritation persists, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.

## 5 Firefighting measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon monoxide (CO)
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Wear protective clothing.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.  
Prevent from spreading (e.g. by damming-in or oil barriers).
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Store in cool, dry place in tightly closed receptacles.  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Handle with care. Avoid jolting, friction and impact.  
Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing or moving, observe grounding/grounding of containers and other equipment when handling.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

**Trade name: R-Y1 Rolmark Yellow Stencil Ink**

(Contd. of page 3)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:**  
Do not store together with oxidizing and acidic materials as well as heavy-metal compounds.  
Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from humidity and water.  
Protect from exposure to the light.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Components with limit values that require monitoring at the workplace:**

### **123-42-2 4-hydroxy-4-methylpentan-2-one**

|     |                                |
|-----|--------------------------------|
| PEL | 240 mg/m <sup>3</sup> , 50 ppm |
| REL | 240 mg/m <sup>3</sup> , 50 ppm |
| TLV | 238 mg/m <sup>3</sup> , 50 ppm |

### **5468-75-7 Yellow AAOT Pigment 14**

|     |  |
|-----|--|
| TLV | Short-term value: 10 as nuisance mg/m <sup>3</sup> |
|-----|--|

### **Modified Rosin Ester NJ TSRN 80100080-5097P EINECS polymer exempt - all components listed**

|     |  |
|-----|--|
| PEL | 5*15** mg/m <sup>3</sup> , 15*50** ppm |
|     | *Respirable Fraction, **Total Dust     |

### **112945-52-5 Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free**

|     |                       |
|-----|-----------------------|
| TLV | 3.5 mg/m <sup>3</sup> |
|-----|-----------------------|

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Pregnant women should strictly avoid inhalation or skin contact.  
Do not eat, drink, smoke or sniff while working.
- **Breathing equipment:**  
Use suitable respiratory protective device in case of insufficient ventilation.  
Use only with adequate ventilation.  
Do not breath vapors, spray mists, or sanding dusts. Use air purifying respirators fitted with organic vapor/HEPA cartridges only if air monitoring demonstrates solvent/particulate levels do not exceed the respirator maximum use concentration. Use properly fitted NIOSH approved respirators. Local and general exhaust should minimize any exposure.

(Contd. on page 5)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

Trade name: R-Y1 Rolmark Yellow Stencil Ink

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Nitrile or natural rubber gloves are typically used to protect from minor contact. Butyl type are best for prolonged contact.

Nitrile rubber, NBR

· **Eye protection:**



Vapor proof safety goggles or full face respirator

· **Body protection:**

Solvent resistant protective clothing

Impervious protective clothing

Tyvek(R) coveralls to protect from light overspray protection or Saranex 23-P(R) for moderate exposure.

## 9 Physical and chemical properties

· **General Information**

· **Appearance:**

|                           |                 |
|---------------------------|-----------------|
| · <b>Form:</b>            | Fluid           |
| · <b>Color:</b>           | Yellow          |
| · <b>Odor:</b>            | Alcohol-like    |
| · <b>Odour threshold:</b> | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

|                                       |                |
|---------------------------------------|----------------|
| · <b>Melting point/Melting range:</b> | Undetermined.  |
| · <b>Boiling point/Boiling range:</b> | 150°C (302 °F) |

· **Flash point:** 58°C (136 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 620°C (1148 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

|                 |           |
|-----------------|-----------|
| · <b>Lower:</b> | 1.4 Vol % |
| · <b>Upper:</b> | 8.1 Vol % |

· **Vapor pressure at 20°C (68 °F):** 1.1 hPa (1 mm Hg)

· **Density at 20°C (68 °F):** 1.13614 g/cm<sup>3</sup> (9.481 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

Trade name: R-Y1 Rolmark Yellow Stencil Ink

(Contd. of page 5)

- |   |  |
|---|--|
| <b>· Solubility in / Miscibility with Water:</b>    | Not miscible or difficult to mix.          |
| <b>· Segregation coefficient (n-octanol/water):</b> | Not determined.                            |
| <b>· Viscosity:</b>                                 |  |
| <b>Dynamic:</b>                                     | Not determined.                            |
| <b>Kinematic:</b>                                   | Not determined.                            |
| <b>· Solvent content:</b>                           |  |
| <b>Organic solvents:</b>                            | 65.7 %                                     |
| <b>VOC content:</b>                                 | 65.7 %                                     |
|   | 746.9 g/l / 6.23 lb/gl                     |
| <b>· Solids content:</b>                            | 34.3 %                                     |
| <b>· Other information</b>                          | No further relevant information available. |

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
Nitrogen oxides  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 123-42-2 4-hydroxy-4-methylpentan-2-one

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | 4000 mg/kg (rat)  |
| Dermal | LD50 | 13630 mg/kg (rab) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**  
Sensitizing effect through inhalation is possible with prolonged exposure.  
Sensitizing effect by skin contact is possible with prolonged exposure.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Danger through skin absorption.

## 12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

**Trade name: R-Y1 Rolmark Yellow Stencil Ink**

(Contd. of page 6)

· **Additional ecological information:**

· **General notes:**

*Water hazard class 1 (Self-assessment): slightly hazardous for water*

*This statement was deduced from the properties of the single components.*

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

*Hand over to hazardous waste disposers.*

*This material and containers that are not empty, if discarded, would be regulated as a hazardous waste under RCRA. Treatment and disposal must be completed at a RCRA permitted treatment, storage, and disposal facility (TSD). The storage and transportation of RCRA hazardous wastes are also regulated by the USEPA.*

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

## 14 Transport information

· **UN-Number**

· **ADR, IMDG, IATA**

1210

· **UN proper shipping name**

· **ADR**

· **IMDG, IATA**

1210 PRINTING INK

PRINTING INK

· **Transport hazard class(es)**

· **DOT**



· **Class**

*Ink, not regulated by Title 49 Part 173.150 Exceptions for Class 3 (flammable) and combustible liquids,(f)(1)*

· **ADR**



· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

(Contd. on page 8)



# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

Trade name: R-Y1 Rolmark Yellow Stencil Ink

(Contd. of page 7)

|  |                                   |
|--|-----------------------------------|
| · <b>Packing group</b>   | III                               |
| · <b>ADR, IMDG, IATA</b>   | III                               |
| · <b>Environmental hazards:</b>  |                                   |
| · <b>Marine pollutant:</b>   | No                                |
| · <b>Special precautions for user</b>  | Warning: Flammable liquids        |
| · <b>Danger code (Kemler):</b>   | 30                                |
| · <b>EMS Number:</b>   | F-E,S-D                           |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                   |
| · <b>UN "Model Regulation":</b>  | UN1148, DIACETONE ALCOHOL, 3, III |

## 15 Regulatory information

## · Sara

· **SARA Title III Section 311/312 - Hazard Communication Standard (40 CFR 370)**

|            |                  |         |
|------------|------------------|---------|
| 13463-67-7 | titanium dioxide | 16.488% |
|------------|------------------|---------|

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed or exempt.

|             |  |  |
|-------------|--|--|
| 123-42-2    | 4-hydroxy-4-methylpentan-2-one   |  |
| 13463-67-7  | titanium dioxide   |  |
| 5468-75-7   | Yellow AAOT Pigment 14   |  |
|             | Modified Rosin Ester NJ TSRN 80100080-5097P<br>EINECS polymer exempt - all components listed |  |
| 7631-86-9   | silicon dioxide, chemically prepared   |  |
| 21645-51-2  | aluminium hydroxide  |  |
|             | acrylic copolymer -EU Polymer exempted- Not Regulated  |  |
| 112945-52-5 | Amorphous Fumed Silica, Silicon Dioxide, Crystalline Free                                    |  |
| 6448-95-9   | Naphthanil Red Pigment C.I. 22   |  |

· **ACGIH Carcinogen**

|            |                  |    |         |
|------------|------------------|----|---------|
| 13463-67-7 | titanium dioxide | A4 | 16.488% |
|------------|------------------|----|---------|

· **Carcinogenity categories**· **IARC (International Agency for Research on Cancer)**

|            |                                      |    |         |
|------------|--------------------------------------|----|---------|
| 13463-67-7 | titanium dioxide                     | 2B | 16.488% |
| 7631-86-9  | silicon dioxide, chemically prepared | 3  | 1.099%  |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

|            |                  |    |         |
|------------|------------------|----|---------|
| 13463-67-7 | titanium dioxide | A4 | 16.488% |
|------------|------------------|----|---------|

· **NIOSH (National Institute for Occupational Safety and Health)**

|            |                                |                   |         |
|------------|--------------------------------|-------------------|---------|
| 123-42-2   | 4-hydroxy-4-methylpentan-2-one | Guidelines 89-104 | 65.74%  |
| 13463-67-7 | titanium dioxide               | *                 | 16.488% |

(Contd. on page 9)



# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/13/2012

Reviewed on 03/13/2012

Trade name: R-Y1 Rolmark Yellow Stencil Ink

(Contd. of page 8)

· **State regulations**

· **New Jersey Right-to-know**

|  |                     |       |
|--|---------------------|-------|
| Modified Rosin Ester NJ TSRN 80100080-5097P<br>EINECS polymer exempt - all components listed | TSRN 80100080-5097P | 3.97% |
|--|---------------------|-------|

· **Massachusetts Right-to-know / Hazardous Substance Codes**

|            |                                      |          |         |
|------------|--------------------------------------|----------|---------|
| 123-42-2   | 4-hydroxy-4-methylpentan-2-one       | 2,4      | 65.74%  |
| 13463-67-7 | titanium dioxide                     | 4        | 16.488% |
| 7631-86-9  | silicon dioxide, chemically prepared | 2,4,5 F5 | 1.099%  |

· **Florida Hazardous / Toxic Substance Lists**

|           |                                      |       |        |
|-----------|--------------------------------------|-------|--------|
| 123-42-2  | 4-hydroxy-4-methylpentan-2-one       | Toxic | 65.74% |
| 7631-86-9 | silicon dioxide, chemically prepared | Toxic | 1.099% |

· **Pennsylvania Hazardous Substances**

|            |                                      |        |         |
|------------|--------------------------------------|--------|---------|
| 123-42-2   | 4-hydroxy-4-methylpentan-2-one       | --     | 65.74%  |
| 13463-67-7 | titanium dioxide                     | Listed | 16.488% |
| 7631-86-9  | silicon dioxide, chemically prepared | Listed | 1.099%  |

· **Minnesota Right To Know / Hazardous Substances**

|            |                                      |                        |         |
|------------|--------------------------------------|------------------------|---------|
| 123-42-2   | 4-hydroxy-4-methylpentan-2-one       | ANO                    | 65.74%  |
| 13463-67-7 | titanium dioxide                     | A                      | 16.488% |
| 7631-86-9  | silicon dioxide, chemically prepared | Codes ANOR, Carcinogen | 1.099%  |

· **Illinois Right To Know**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Xi Irritant

· **Risk phrases:**

36 Irritating to eyes.

· **Safety phrases:**

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36 Wear suitable protective clothing.

51 Use only in well-ventilated areas.

60 This material and its container must be disposed of as hazardous waste.

· **National regulations:**

· **Occupational Safety and Health Act (OSHA)**

Immediate (acute) health hazard

Delayed (chronic) Health Hazard

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

## 16 Other information

(Contd. on page 10)

USA

**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 03/13/2012

Reviewed on 03/13/2012

**Trade name: R-Y1 Rolmark Yellow Stencil Ink**

(Contd. of page 9)

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**· Relevant phrases**

H319 Causes serious eye irritation.

R36 Irritating to eyes.

**· Contact: Mike Rickert****· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA